

Electricals Electronics Enterprises, India.

No. 172, Thambu Chetty Street, Parrys, Chennai 600 001.


Ph.: 044-42164501 Telefax: 044-42164502

Email: measurecurrent@gmail.com

PH-80

PH-80: pH HydroTester





The PH-80 has proven to be the MOST reliable pH meter in its price range. It has become a favorite in such applications as hydroponics & gardening, pools & spas, aquariums & reef tanks, water ionizers, drinking water and more.

FEATURES:

- Measures pH and Temperature
- One-touch automatic digital calibration
- Water resistant
- Simultaneous temperature display
- Large LCD display
- Automatic Temperature Compensation (ATC)
- Auto-off function, data-hold function and low-battery indicator
- Factory Calibrated: The PH-80 meter is factory calibration to pH 7.0.
- Includes a translucent cap, batteries, storage solution and pH 7.0 buffer (powder)

PRODUCT DESCRIPTION

- pH Range: 0 – 14
- Temperature Range: 1-55 °C; 32-130 °F
- Resolution: 0.1 pH; Temperature resolution is 0.1 °C/F
- Accuracy: +/- 0.2 pH; Temperature accuracy is +/-2%
- Calibration: Digital automatic calibration (one point)
- Minimum EC/TDS: 10 µS/5 ppm
- Electrode: Glass sensor and reference tube electrodes
- Power source: 3 x 1.5V button cell batteries (model LR44 or equivalent; included)
- Dimensions: 15.3 x 3.2 x 1.8 cm (6.0 x 1.3 x 0.7 inches)
- Weight: 53.9 g (1.9 oz)
- UPC: 891144000175