

# Flue gas analyzer for industry

**testo 340 – Portable measuring instrument for industrial emission measurement**

---

Measuring range extension for unrestricted measurement at high gas concentrations

---

Flue gas analysis with up to 4 gas sensors – freely configurable

---

Large selection of probes

---

Bluetooth interface

---

Convenient measurement data management

---

TÜV-tested /EN norm



The handy, easy-to-operate emission measuring instrument testo 340 is the right tool for many different emission measurements. The compact design and the reliable technology make it the ideal measuring instrument for commissioning, service and maintenance work and in test measurements on industrial burners, stationary industrial engines, gas turbines and thermal processes.

The unique measuring range extension allows unrestricted measurements to be carried out even at high gas concentrations. The testo 340 is equipped with an O<sub>2</sub> sensor as standard. Three further gas sensors can be configured individually, in order to be able to adapt the instrument optimally to the respective measurement task. The instrument can also be operated remotely from your Android Smartphone or tablet using the free App.

## Ordering data

### testo 340

testo 340 flue gas analyzer, incl. rechargeable battery, calibration protocol and carrying strap, equipped with O<sub>2</sub> sensor, integrated flow/differential pressure measurement

Part no. 0632 3340



testo 340 must be equipped with a second gas sensor otherwise the analyzer cannot function. Max. 3 additional sensors can be fitted.

#### Options

#### Part no.

Option CO sensor, 0 to 10000 ppm, Resolution 1 ppm

Option COlow sensor, 0 to 500 ppm, Resolution 0.1 ppm

Option NO sensor, 0 to 4000 ppm, Resolution 1 ppm

Option NO<sub>low</sub> sensor, 0 to 300 ppm, Resolution 0.1 ppm

Option NO<sub>2</sub> sensor, 0 to 500 ppm, Resolution 0.1 ppm

Option: SO<sub>2</sub> sensor, 0 to 5,000 ppm, Resolution 1 ppm

Option: BLUETOOTH® module

Option: dilution of all sensors

#### Accessories

#### Part no.

Transport case for flue gas analyzer and probes

0516 3400

Mains unit international 100-240 V AC / 6.3 V DC for mains operation or battery charging in instrument, for mains operation or battery charging in instrument

0554 1096

Software „easyEmission“, incl. USB connection cable instrument-PC

0554 3334

Multiple license/“easyEmission“ software

0554 3338

Testo fast printer IrDA with wireless infrared interface; 1 roll thermal paper; 4 AA batteries

0554 0549

Testo Bluetooth®/IRDA printer incl. 1 roll of printer paper, rechargeable battery and mains unit

0554 0620

Spare thermal paper for printer, permanent ink

0554 0568

Spare rechargeable battery with charger

0554 1087

Replacement filter for NO sensor (1 pcs.), blocks transverse gas SO<sub>2</sub>

0554 4150

Replacement CO sensor (1 off.), blocks transverse gas SO<sub>2</sub> and NO

0554 4100

#### Calibration Certificates

#### Part no.

ISO calibration certificate/flue gas

0520 0003

ISO calibration certificate velocity, hot wire, vane anemometer, Pitot tube; calibration points 5; 10; 15; 20 m/s

0520 0034

## Ordering suggestions

### Your low-budget entry into industrial emission measurement

Part no.	
testo 340 flue gas analyzer	0632 3340
Option CO (H2-compensated) measurement module, 0 to 10,000 ppm	
Option BLUETOOTH® module	
Flue gas probe modular 335 mm immersion depth	0600 9766
International mains unit 100-240 V	0554 1096
testo BLUETOOTH® printer	0554 0620
Transport case for measuring instrument and probes	0516 3400

### Monitoring and adjustment work on stationary industrial engines

Part no.	
testo 340 flue gas analyzer	0632 3340
Option CO (H2-compensated) measurement module, 0 to 10,000 ppm	
Option NO measurement module, 0 to 4,000 ppm	
Option NO <sub>2</sub> measurement module, 0 to 500 ppm	
Option dilution of all sensors	
Flue gas probe for industrial engines, 335 mm immersion depth*	0600 7555
International mains unit 100-240 V	0554 1096
Software „easyEmission“	0554 3334
Transport case for measuring instrument and probes	0516 3340

\* For measurement on stationary diesel engines, we recommend the flue gas probe with probe pre-filter (0600 7556).

### Service and maintenance work on industrial burners and furnaces

Part no.	
testo 340 flue gas analyzer	0632 3340
Option CO (H2-compensated) measurement module, 0 to 10,000 ppm	
Option NO measurement module, 0 to 4,000 ppm*	
Option SO <sub>2</sub> measurement module, 0 to 5,000 ppm	
Flue gas probe modular 700 mm immersion depth	0600 8765
Software „easyEmission“	0554 3334
Transport case for measuring instrument and probes	0516 3340

\*For the measurement of low NO values, we recommend the NOlow sensor (0393 1152).

### Measurements on turbines

Part no.	
testo 340 flue gas analyzer	0632 3340
Option CO (H2-compensated) measurement module, 0 to 10,000 ppm*	
Option NOlow measurement module, 0 to 300 ppm	
Option NO <sub>2</sub> measurement module, 0 to 500 ppm	
Option dilution of all sensors	
Flue gas probe for industrial engines, 335 mm immersion depth	0600 7555
International mains unit 100-240 V	0554 1096
Software „easyEmission“	0554 3334
Transport case for measuring instrument and probes	0516 3340

\*For the measurement of low CO values, we recommend the COlow sensor (0393 1102).

# Gas sampling probes

## Standard gas sampling probes: Modular flue gas probes, available in 2 lengths, incl. probe stop, NiCr-Ni thermocouple, 2.2 m hose and particle filter

	Part no.
Modular flue gas probe 335 mm immersion depth, incl. cone, thermocouple NiCr-Ni (Tl) Tmax 500 °C and NO <sub>x</sub> /SO <sub>2</sub> special hose 2.2 m	0600 9766
Modular flue gas probe 700 mm immersion depth, incl. cone, thermocouple NiCr-Ni (Tl) Tmax 500 °C and NO <sub>x</sub> /SO <sub>2</sub> special hose 2.2 m	0600 9767
Modular flue gas probe 335 mm immersion depth, incl. cone, thermocouple NiCr-Ni (Tl) Tmax 1000 °C and NO <sub>x</sub> /SO <sub>2</sub> special hose 2.2 m	0600 8764
Modular flue gas probe, 700 mm immersion depth, incl. cone, thermocouple NiCr-Ni (Tl) Tmax 1000 °C and NO <sub>x</sub> /SO <sub>2</sub> special hose 2.2 m	0600 8765
Modular flue gas probe with pre-filter Ø 14 mm 335 mm immersion depth, incl. cone, thermocouple NiCr-Ni (Tl) Tmax 1000°C and NO <sub>x</sub> /SO <sub>2</sub> special hose 2.2 m	0600 8766
Modular flue gas probe with pre-filter Ø 14 mm 700 mm immersion depth, incl. cone, thermocouple NiCr-Ni (Tl) Tmax 1000°C and NO <sub>x</sub> /SO <sub>2</sub> special hose 2.2 m	0600 8767

## Probe accessories modular gas sampling probes

	Part no.
Hose extension; 2.8 m; extension cable for probe	0554 1202
Probe shaft with pre-filter Ø 14 mm, length selectable up to 2500 mm, incl. cone, Ø 8 mm, thermocouple NiCr-Ni (Tl) Tmax. 500 °C	On request
Probe shaft with pre-filter Ø 14 mm, length selectable up to 2500 mm, incl. cone, Ø 8 mm, thermocouple NiCr-Ni (Tl) Tmax. 1000 °C	On request
Spare probe pre-filter (sinter filter) 2 off	0554 3372
Spare dirt filter, modular probe; 10 off	0554 3385
Probe shaft, length 700 mm, incl. cone, Ø 8 mm, Tmax 500 °C	0554 9767
Probe shaft, length 335 mm, incl. cone, Ø 8 mm, Tmax 1000 °C	0554 8764
Probe shaft, length 700 mm, incl. cone, Ø 8 mm, Tmax. 1000 °C	0554 8765

## Gas sampling probe for measurement on industrial engines

	Part no.
Flue gas probe for industrial engines, 335 mm immersion depth incl. probe stop and heat protection plate, Tmax. +1,000 °C, special hose for NO <sub>x</sub> /SO <sub>2</sub> measurements, length 4 m	0600 7555
Flue gas probe for industrial engines with probe shaft preliminary filter, 335 mm immersion depth incl. probe stop and heat protection plate, Tmax. +1,000 °C, special hose for NO <sub>x</sub> /SO <sub>2</sub> measurements, length 4 m	0600 7556
Thermocouple for flue gas temperature measurement, NiCr-Ni, length 400 mm, Tmax +1,000 °C, with 4 m connecting cable and additional heat protection	0600 8898

## Temperature probes

	Part no.
Mini ambient air probe; for separate ambient air temperature measurement; 0 to +80 °C	0600 3692
Combustion air temperature probe, immersion depth 60 mm	0600 9797

## Pitot tubes

	Part no.
Pitot tube, 350 mm long, stainless steel, measures flow velocity	0635 2145
Pitot tube, 1000 mm long, stainless steel, measures flow velocity	0635 2345
Connection hose; silicone; length 5 m; max. load 700 hPa (mbar)	0554 0440
Pitot tube, stainless steel, 750 mm long, measures flow velocity with temperature, 3x hoses (5 m long) and heat shield	0635 2042

# Gas sampling probes

Industrial probes	Details	Part no.
Industrial probe set 1200 °C consisting of: - unheated handle - unheated probe shaft up to 1200 °C flue gas temperature - unheated gas sampling hose incl. inline filter, length 4 m - thermocouple Type K, length 1.2 m  The set can optionally come with an extension tube and probe preliminary filter.	Probe shaft: $T_{max.} +1200 \text{ }^{\circ}\text{C}$ Length 1.0 m, Ø 12 mm Material 2.4856 alloy 625 Handle: $T_{max.} +600 \text{ }^{\circ}\text{C}$ Material: 1.4404 stainless steel Gas sampling hose: 2-chamber hose with PTFE inner core; length 4.0 m TC: Type K, Length 1.2 m, Ø 2 mm $T_{max.} +1200 \text{ }^{\circ}\text{C}$	0600 7610
Industrial probe set 1800 °C consisting of: - unheated handle - unheated probe shaft up to 1800 °C flue gas temperature - unheated gas sampling hose incl. inline filter, length 4 m  For temperature measurements $> +1370 \text{ }^{\circ}\text{C}$ , we recommend a thermocouple Type S.	Probe shaft: $T_{max.} +1800 \text{ }^{\circ}\text{C}$ Material Al2O3 > 99.7% Length 1.0 m, Ø 12 mm Gas sampling hose: 2-chamber hose with PTFE inner core; length 4.0 m Handle: $T_{max.} +600 \text{ }^{\circ}\text{C}$ Material: 1.4404 stainless steel	0600 7620
Heated industrial probe set consisting of: - heated probe shaft up to 600 °C flue gas temperature - heated gas sampling hose, length 4 m - thermocouple Type K, length 1.2 m  The set can optionally come with an extension tube and probe preliminary filter.	Probe shaft: temperature-proof up to +600 °C Voltage supply 230 V / 50 Hz Length 1.0 m, Ø 25 mm Heating temperature range +200 °C Material stainless steel 1.4571 Gas sampling hose: corrugated hose with PTFE inner core Length 4.0 m; outside diameter 34 mm Heating temperature range $> +120 \text{ }^{\circ}\text{C}$ TC: Type K Length 1.2 m, Ø 2 mm $T_{max.} +1200 \text{ }^{\circ}\text{C}$	0600 7630
Extension tube 1200 °C for extending the industrial probe set 1200 °C (0600 7610) and heated industrial probe set (0600 7630)  The extension tube can be screwed directly onto the unheated probe shaft up to +1200 °C and the heated probe shaft up to +600 °C.*	Probe shaft: $T_{max.} +1200 \text{ }^{\circ}\text{C}$ Length 1.0 m, Ø 12 mm Material 2.4856 alloy 625	0600 7617
Thermocouple Type K, length 2.2 m	Type K Length 2.2 m, Ø 2 mm $T_{max.} +1200 \text{ }^{\circ}\text{C}$	0600 7615
Industrial probe preliminary filter for dust-laden flue gas  The probe preliminary filter can be screwed directly onto the unheated probe shaft up to +1200 °C and the heated probe shaft up to +600 °C.*	Material porous silicon carbide $T_{max.} +1,000 \text{ }^{\circ}\text{C}$ , Length 105 mm, Ø 30 mm Filtration grade 10 µm	0600 7616
Heated gas sampling hose	Corrugated hose with PTFE inner core Length 4.0 m; outside diameter 34 mm Heating temperature range $> +120 \text{ }^{\circ}\text{C}$	on request
Transport case for probes Suitable for all probes with a total length $> 335 \text{ mm}$ .		0516 7600
Extension cable, 5 m long, between plug-in head cable and instrument		0409 0063
Spare dirt filter (10 off)		0554 3371

\*For ease of tightening and releasing, we recommend the use of ceramic paste on the thread. This is available from retailers.