ELECTRICALS ELECTRONICS ENTERPRISES

NO. 172, Thambu Chetty Street, Parrys, Chennai www.measurecurrent.in



UNI-T 210E CLAMP METER.

Features

- 1. VFC, low pass filter
- 2. NCV
- 3. Ergonomic and lightweight
- 4. Auto range, 2~3/s sampling rate
- 5. True RMS
- 6. ZERO mode
- 7. LCD backlight, data hold
- 8. Auto power off, low battery indication














ntertek

Specifications	Range	Best Accuracy
Model		UT210E
AC Current (A)	2A/20A/100A	±(2.5%+5)
DC Current (A)	2A/20A/100A	±(2%+3)
AC Voltage (V)	2V/20V/200V/600V	±(1%+3)
DC Voltage (V)	200mV/2V/20V/200V/600V	±(0.7%+3)
Resistance (Ω)	$200\Omega/2$ kΩ/ 20 kΩ/ 200 kΩ/ 2 MΩ/ 20 MΩ	±(1%+2)
Capacitance (F)	2nF/20nF/200nF/2μF/20μF/200μF/2mF/20mF	±(4%+5)
Features		
Display Count		2000
Auto Range		V
Jaw Capacity		17mm
True RMS		V
Diode	Around 3.0V	V
V.F.C.		V
NCV		V
Auto Power Off	Around 15 minutes	V
Continuity Buzzer		V
Low Battery Indication	≤2.5V	V
Data Hold		V
Zero Mode		1
LCD Backlight		$\sqrt{}$

Input Protection		√	
Input Impedance for DCV	≥10MΩ	V	
General Characteristics			
Power	AAA 1.5V x 2		
LCD Size	39.3mm x 26.5mm		
Product Color	Red and grey		
Product Net Weight	170g		
Product Size	175mm x 60mm x 33.5mm		
Standard Accessories	Batteries, Test Leads		
Standard Individual Packing	Gift Box, Carrying bag, English Manual		

Also we suggest you to visit our website www.measurecurrent.in we have over 350 Instruments on Display.

Thanks,

Electricals Electronics Enterprises
No.172 Thambu Chetty Street, Parrys, Chennai-01
9840178601.
measurecurrent@gmail.com
www.measurecurrent.in